



ACCURATE & EASY TO USE

Discover a wide selections of our
sound measurement equipments according to your
sound measurement needs

PHANTOM PCR SERIES MICROPHONES
PCR 11 / 22 / 30 / 24 / 45

www.placidinstruments.com



PLACID INSTRUMENTS BV

Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS

Phone Landline: +31 302106021

Worldwide (except Europe): +31 613915102

Europe: +31 622813335

info@placidinstruments.com

www.placidinstruments.com

PLACID Phantom PCR Series Microphones

PCR PH

ENGINEERING RECORDING-TEST MICROPHONE



PCR11



PCR22



PCR45

PCR series microphones are phantom powered measurement-level studio microphones which have 3-pin XLR. According to the diameter of capsules, PCR series include 1" 1/2" and 1/4" studio microphones. Each type microphone has special characteristic, such as different Max Sound Level, Sensitivity, Frequency, and Inherent Noise, etc.

Nickle diaphragm coated with quartz

Omnidirectional and high sensitivity

Excellent suitable for concert halls & spot miking for acoustical instruments

Precise detailed and natural reproduction



PLACID INSTRUMENTS BV

Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS

Phone Landline: +31 302106021

Worldwide (except Europe): +31 613915102

Europe: +31 622813335

info@placidinstruments.com

www.placidinstruments.com

Specification



Type	PCR11	PCR22	PCR30	PCR24	PCR45
POLAR PATTERN			Omni		
SENSITIVITY	-24 dB	-28 dB	-30 dB	-36 dB	-52 dB
FREQUENCY RANGE	20~20K	20~20K	20~20K	20~40K	20Hz~50K
OUTPUT IMPEDANCE	220 Ω				
ELEMENT	Prepolarized				
MAXIMUM INPUT SOUND LEVEL (1%THD@1KHZ)	130 dB	140 dB	130 dB	155 dB	160 dB
SELF NOISE	18 dB(A)	18 dB(A)	22 dB(A)	20 dB(A)	30 dB(A)
SUPPLY VOLTAGE (P48, IEC 61938)	48 V				
MICROPHONE DIAMETER (INCH)	1"	1/2"	1/2"	1/2"	1/4"
SOUND FIELD	Free-field				
TYPICAL SENSITIVITY (MV/PA)	60	40	30	12	4
DIAPHRAGM	Nickel	Nickel	Nickel	Nickel	Nickel
CLASS	1	1	2	1	1