



ACCURATE & EASY TO USE

Discover a wide selections of our
sound measurement equipments according to your
sound measurement needs

PAVEMENT ABSORPTION
PLACID PRA 089

www.placidinstruments.com



PLACID INSTRUMENTS BV

Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS

Phone Landline: +31 302106021

Worldwide (except Europe): +31 613915102

Europe: +31 622813335

info@placidinstruments.com

www.placidinstruments.com



PLACID

Pavement Absorption

PLACID PRA 089 Pavement Absorption
ISO13472-2:2010 ISO10844

Road Surface Absorption Measurement System

Measure road surface sound absorption in situ in according to ISO 13472-2:2010.

The ISO 13472-2:2010 describes the test method for measuring in situ sound absorption coefficient of road surfaces for the one-third octave-band frequencies ranging from 250 Hz to 1800 Hz under normal incidence conditions. For special purposes, the frequency range can be adjusted by modifying the dimensions of the system..

Features

- Turnkey solution system
- One carrying case for the complete system
- Heavy-duty grade aluminium tube
- Stainless steel reflection reference
- USB DAQ low distortion power amplifier
- Plug and Play system
- Realtime data analysis monitoring
- Processing and analysis according to ISO 13472, ISO 10534, GB/T 18696
- Easy data export to Excel
- Automatic broadband noise generator

