



PLACID
MICROPHONE
PREAMPLIFIER

**PNP
41**

ACCURATE & STABLE

PLACID MEASUREMENT MICROPHONES

Discover a wide selection of our measurement microphones according to your sound measurement needs

Placid Instruments BV

Newtonlaan 115

Office No. 2.21

3584 BH UTRECHT

THE NETHERLANDS

info@placidinstruments.com

www.placidinstruments.com

ASK US!
HERE





PLACID INSTRUMENTS BV

Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS

Phone +31 302106021

email info@placidinstruments.com

website www.placidinstruments.com

PLACID PNP41

1/4" STANDARD PREAMPLIFIER



Specification

Frequency Range

5.0 Hz to 100 kHz

Noise

< 2.5 μ V

Usage

General purpose

The PLACID PNP41 1/4" Preamplifier is a robust preamplifier designed to be used for acoustic measurements with condenser microphones. The self-noise is very low, it has a wide dynamic range and frequency response.



PLACID INSTRUMENTS BV

Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS

Phone +31 302106021

email info@placidinstruments.com

website www.placidinstruments.com

Specification

Design

All PLACID ICCP microphone preamplifiers are designed for ¼", ½" and 1" condenser microphones.

The preamplifiers are optimized to have a flat frequency response which will ensure high quality acoustic measurements.

Self Noise

The electrical circuit has especially been designed to ensure a low self-noise level which typically be much lower than the self-noise of the microphone cartridge.

Impedance

The PLACID PNP41 input impedance is over 5 Ω , the output impedance is less than 110 Ω .

Daily usage

- General-purpose preamplifier
- High-frequency measurements
- High-pressure measurements



PLACID INSTRUMENTS BV

Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS

Phone +31 302106021

email info@placidinstruments.com

website www.placidinstruments.com

DATASHEET PLACID PNP41 PREAMPLIFIER



Frequency Response (Ref. 250 Hz, 0.2 dB)	Hz	5.0 to 100 kHz
Slew Rate	V/ μ s	2.95
Input Impedance	G Ω	\gg 1.5
Output Impedance	Ω	< 110
Max Output Voltage	V _{rms}	8.0
Noise (A-Weighted)	μ V	< 2.5
Noise (Linear 20 Hz – 20 kHz)	μ V	< 6.0
Gain	dB	- 0.18
DC – offset, minimum	V	15
DC- offset, maximum	V	24
Power Requirement	mA	ICP 2 to 20
Temperature operational range	Celcius	- 40 to 100
Temperature storage range	Celcius	-40 to 100
Humidity operational range noncondensing	% Rh	0 to 98
Output Connector Type		SMB
Diameter	Inch	¼
Weight	Gram	6.5
Length	mm	58.0



Placid Instruments BV

Newtonlaan 115, Office No. 2.21

3584 BH UTRECHT

THE NETHERLANDS

Phone landline : +31 302106021

Email : info@placidinstruments.com

www.placidinstruments.com

ASK US!
HERE

