



ACCURATE & EASY TO USE

Discover a wide selections of our
sound measurement equipments according to your
sound measurement needs

PQ 1601

16-CHANNEL BNC
CONNECTOR

www.placidinstruments.com



PLACID INSTRUMENTS BV

Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS

Phone +31 302106021

email info@placidinstruments.com

website www.placidinstruments.com

PLACID 16-CHANNEL BNC CONNECTOR PQ1601





PLACID INSTRUMENTS BV

Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS

Phone +31 302106021

email info@placidinstruments.com

website www.placidinstruments.com

DATASHEET PLACID PQ1601



Input Channels	16-Channel BNC interface
PC Connection Method	USB
Programable Gain	x1, x10, x100
IEPE Current	4 mA
Sampling Rate (Hz)	(1-100) kHz
Dynamic Range (dB)	112 dB
Accuracy	0.3%
N of conversion bits	24 bits
Frequency response	5 ~ 20000 Hz(± 0.5 dB ref 1000Hz)
Dynamic range A-Weighted	120 dB
Input Impedance	10 M Ω
Self Noise	<0.03 mVrms
A/D convertor	Delta-Sigma
Power Consumption	6.6 W



Placid Instruments BV

Newtonlaan 115, Office No. 2.21

3584 BH UTRECHT

THE NETHERLANDS

Phone landline : +31 302106021

Email : info@placidinstruments.com

www.placidinstruments.com

ASK US!
HERE

